

Gryphon™ Desk 2D Plus ESD

General Purpose Corded Handheld Area Imager Bar Code Reader for Electrostatic Discharge Control



Features

- Certified between static dissipative (106 Ω and 1012 Ω) and conductive (103 Ω and 106 Ω) range 16.5 kV Electrostatic protection (air discharge)
- Omnidirectional reading
- Advanced 'motion tolerance' optics
- Supports 1D, 2D and postal codes
- plus stacked and composite codes like PDF417 and GS1 DataBar™
- Datalogic's patented 'Green Spot' for good-read feedback and instinctive 5-dot aimer

With rich feature sets and extensive model options, the Gryphon product series from Datalogic Scanning represents the premium level of data collection equipment for general purpose applications. The Gryphon D432 Plus ESD reader has been specially developed by Datalogic Scanning to satisfy the strict requirements for EPA (ESD Protected Area) use. ESD is a phenomenon that occurs when an object has an imbalance in its electrical charge: a fast charge transfer between objects with differing electrostatic potential caused by contact or by the proximity of the two objects.

Wherever electronic components are handled, installed or assembled, ESD poses a threat to product quality. With technological advances

in electronics an increasing number of these components are susceptible to damage or destruction by increasingly lower voltage levels. ESD events can also compromise the measurements taken by very sensitive instruments, like those used in hospital and medical analysis laboratories. The most advanced polymer and elastomeric technologies are used for the ESD-safe Gryphon D432 Plus reader.

The body of the product is composed of a slightly conductive plastic, rather than an insulating one, preventing the accumulation of tribocharges. Specific cables additionally guarantee ESD safety between any two points. These specialized protective features are added to the same outstanding reading snappi-

ness and full 2D decoding capability of Gryphon D432 Plus. Enhanced optics with improved 'motion tolerance' allows codes placed on fast moving objects to be easily and quickly captured, creating the ideal reader for tasks requiring high throughput like those found in light industrial manufacturing environments.

The Gryphon D432 Plus ESD features Datalogic's exclusive patented 'Green Spot' providing good read feedback directly on the code which is especially useful for noisy environments. Aiming at the image to be captured is easy and intuitive, with the single click trigger that enables the Datalogic 5-dot aimer, marking the four corners and center of the reading area.



Mounts/Stands

- 90ACC1760 Hands Free Stand (STDGRYPHON) for Gryphon Dx000/D110/Mx00, DLC707x-M1
- 90ACC1770 Desk/Wall Holder (SPCGRYPHON)
- 90ACC1873 Hands Free Stand (STD-1010) for Gryphon Dx20/BTx00
- 90ACC1876 PLATE, Metal Plate for STDGryphon, STD-10xx

Specifications

Decoding Capability

1D/ Linear Codes
 2D Codes
 Postal Codes

Stacked Codes

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes
 Aztec Code; Data Matrix; MaxiCode; QR Code
 Australian Post; China Post; Japanese Post; KI X Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
 EAN/JAN Composites, GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

Electrical

Current
 Input Voltage

Current Operating (Typical): 245 mA @ 5 VDC ; Standby/Idle (Typical): 120 mA @ 5 VDC
 4.75 - 5.25 VDC

Environmental

Ambient Light
 Drop Resistance
 ESD Features

0 - 100,000 lux
 Withstands repeated drops from 1.2 m / 3.9 ft onto a concrete surface
 Certification Rank: Certified between static dissipative (106 Ω and 1012 Ω) and conductive (103 Ω and 106 Ω) range
 Residual Voltage: < 5 V

ESD Protection (Air Discharge)
 Humidity (Non-condensing)
 Particulate and Water Sealing
 Temperature

16.5 kV
 0 - 95%
 IP30
 Operating: 0 to 50 °C / 32 to 122 °F
 Storage/Transport: -40 to 70 °C / -40 to 158 °F
 Keyboard Wedge; RS-232; USB, Wand

Interfaces

Physical Characteristics

Colors Available
 Dimensions
 Weight

Black
 17.9 x 8.1 x 9.8 cm / 7.0 x 3.2 x 3.9 in
 198.0 g / 7.0 oz

Reading Performance

Image Capture
 Imager Sensor
 Light Source
 Print Contrast Ratio (Minimum)
 Reading Angle
 Reading Indicators
 Resolution (Maximum)

Wide VGA: 752 x 480 pixels ; Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
 2D CMOS Array: 752 x 480 pixels
 Aiming: 630 - 670 nm VLD
 23%
 Angle Pitch: 35°; Roll (Tilt): +/- 360°; Skew (Yaw): +/- 40°
 Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback; Good Read LED
 Data Matrix: 0.076 mm / 3 mils; Linear: 0.100 mm / 4 mils

Reading Ranges

Typical Depth of Field

Minimum distance determined by symbol length and scan angle.
 Printing resolution, contrast, and ambient light dependent.
 10 mils Data Matrix: 1.5 to 14.0 cm / 0.6 to 5.5 in
 10 mil PDF: 0.5 to 22.0 cm / 0.2 to 8.6 in
 EAN13 - 13 mils: 1.5 to 22.0 cm / 0.6 to 8.6 in

Safety & Regulatory

Agency Approvals
 Environmental Compliance
 Laser Classification

The product meets necessary safety and regulatory approvals for its intended use.
 Complies to China RoHS; Complies to EU RoHS
 Caution Laser Radiation - Do not stare into beam; CDRH Class II; IEC 60825 Class 2

LED Classification

IEC 60825 Class 1 LED

Utilities

Datalogic Aladdin™

Datalogic Aladdin configuration program is available for download at no charge

Warranty

5-Year Factory Warranty