

XENON EXTREME PERFORMANCE (XP) 1950h

Corded Area-Imaging Scanner

The most successful and discerning healthcare providers choose Xenon™ scanners to ensure they are delivering more meaningful patient interactions and clinical outcomes.

The Xenon Extreme Performance (XP) 1950h scanner builds on the strong foundation of earlier Xenon healthcare scanners, continuing the tradition of industry-leading performance and reliability.

The Xenon XP 1950h healthcare scanner ensures that healthcare professionals remain focused on the patient, making the process of patient ID verification quick and easy. Incorporating Honeywell's renowned imaging technology, the Xenon XP 1950h scanner offers superior scan performance, easily capturing even the most difficult-to-read or damaged codes. This helps to eliminate wasted movements and lost time, improving healthcare worker productivity and throughput.

Engineered to 50 drops at 1.8 m (6 ft) and 2,000 tumbles at 0.5 m (1.6 ft), and with an IP52 ingress rating for water and dust, the Xenon XP 1950h scanner's class-leading reliability reduces scanner downtime and service costs, leading to a longer lifecycle and lower total cost of ownership.



The Xenon XP 1950h scanner delivers premium performance and class-leading durability for increased clinician productivity and maximum uptime - improving patient outcomes and lowering TCO.

FEATURES AND BENEFITS



Superior 1D and 2D scanning performance, even on damaged and poor-quality barcodes, eliminates wasted seconds from any scan.



The disinfectant-ready plastic housing protects your investment with a durable construction engineered to resist the harmful effects of harsh chemicals.



Multiple patient comfort modes are available to ensure patient comfort while maintaining clinician productivity: Patient Do-Not-Disturb, Vibration, and Scan Lamp.



Honeywell Operational Intelligence software delivers on-demand scan insights, enabling higher healthcare worker productivity and throughput.



The Honeywell Scanner Management Utility (SMU) creates a holistic solution that automates how you deploy and update the scanners in your environment.

Honeywell

Xenon Extreme Performance (XP) 1950h Technical Specifications

MECHANICAL/ELECTRICAL

Dimensions (L x W x H): 104.1 mm x 71.1 mm x 160 mm (4.1 in x 2.8 in x 6.3 in)

Scanner Weight: 147.42 g (5.2 oz)

Input Voltage: 4.4V DC – 5.5V DC

Operating Power (Charging) Bases: 2.5W (500 mA @ 5V DC)

Host System Interfaces: USB, Keyboard Wedge, RS-232, RS485 support for TGCS (IBM) 46XX

User Indicators: Good Decode LEDs, Rear View LEDs, Beeper (adjustable tone and volume), Vibration (optional)

ENVIRONMENTAL

Operating Temperature: 0° C to 50° C (32° F to 122° F)

Storage Temperature: -40° C to 70° C (-40° F to 158° F)

Electrostatic Discharge (ESD) (Scanners and Cradles): ±8 kV indirect coupling plane, ±15 kV direct air

Humidity: 0% to 95% relative humidity, non-condensing

Tumble Spec: 2,000 0.5 m (1.6 ft) tumbles (impacts)

Drop: Engineered to withstand 50 1.8 m (6 ft) drops to concrete

Environmental Sealing: IP52

Light Levels: 0 to 100,000 lux (9,290 foot-candles)

SCAN PERFORMANCE

Scan Pattern: Area Image (1280 x 800 pixel array)

Motion Tolerance: Up to 400 cm/s (157 in/s) for 13 mil UPC at optimal focus

Scan Angle

SR: Horizontal: 48°; Vertical: 30°

HD: Horizontal: 48°; Vertical: 30°

Print Contrast: 20% minimum reflectance difference

Roll, Pitch, Skew: ±360°, ±45°, ±65°

Decode Capabilities: Reads standard 1D, PDF, 2D, Postal Digimarc, DOT Code, and OCR symbologies

Note: Decode capabilities dependent on configuration

Warranty: 5-year factory warranty



For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.

Xenon is a trademark or registered trademark of Honeywell International Inc.

All other trademarks are the property of their respective owners.

DECODE RANGES (DoF)

TYPICAL PERFORMANCE*	STANDARD RANGE (SR)	HIGH DENSITY (HD)
NARROW WIDTH		
3 mil Code 39	57 mm - 141 mm (2.2 in - 5.6 in)	29 mm - 138 mm (1.1 in - 5.4 in)
5 mil Code 39	28 mm - 253 mm (1.1 in - 10 in)	16 mm - 219 mm (0.6 in - 8.6 in)
10 mil Code 39	0 mm - 473 mm (0 in - 18.6 in)	0 mm - 371 mm (0 in - 14.6 in)
13 mil UPC	0 mm - 495 mm (0 in - 19.5 in)	0 mm - 366 mm (0 in - 14.4 in)
15 mil Code 128	0 mm - 557 mm (0 in - 21.9 in)	0 mm - 423 mm (0 in - 16.7 in)
20 mil Code 39	3 mm - 829 mm (0.1 in - 32.6 in)	4 mm - 620 mm (0.2 in - 24.4 in)
5 mil PDF417	54 mm - 160 mm (2.1 in - 6.3 in)	31 mm - 157 mm (1.2 in - 6.2 in)
6.7 mil PDF417	34 mm - 221 mm (1.3 in - 8.7 in)	16 mm - 212 mm (0.6 in - 8.3 in)
7.5 mil DM**	50 mm - 182 mm (2 in - 7.2 in)	28 mm - 169 mm (1.1 in - 6.7 in)
10 mil DM**	27 mm - 249 mm (1.1 in - 9.8 in)	11 mm - 214 mm (0.4 in - 8.4 in)
20 mil QR	0 mm - 453 mm (0 in - 17.8 in)	0 mm - 328 mm (0 in - 12.9 in)

* Performance may be impacted by barcode quality and environmental conditions.

** Data Matrix (DM)

XENON EXTREME PERFORMANCE (XP) 1952h

Cordless Area-Imaging Scanner

The most successful and discerning healthcare providers choose Xenon™ scanners to ensure they are delivering more meaningful patient interactions and clinical outcomes.

The Xenon Extreme Performance (XP) 1952h scanner builds on the strong foundation of earlier Xenon healthcare scanners, continuing the tradition of industry-leading performance and reliability.

The Xenon XP 1952h healthcare scanner ensures that healthcare professionals remain focused on the patient, making the process of patient ID verification quick and easy. Incorporating Honeywell's renowned imaging technology, the Xenon XP 1952h scanner offers superior scan performance, easily capturing even the most difficult-to-read or damaged codes. This helps to eliminate wasted movements and lost time, improving healthcare worker productivity and throughput.

Freedom of movement around patients, family members, and expensive equipment – particularly in congested patient rooms or ICUs – is a continued challenge for today's clinician. As more and more technology is packed into the modern-day patient room, free space comes at a premium. The Xenon XP 1952h cordless scanner ensures nurses' focus is on patient safety and comfort.

Engineered to 50 drops at 1.8 m (6 ft) and 2,000 tumbles at 0.5 m (1.6 ft), the Xenon XP 1952h scanner's class-leading reliability reduces scanner downtime and service costs, leading to a longer lifecycle and lower total cost of ownership.



The Xenon XP 1952h scanner delivers premium performance and class-leading durability for increased clinician productivity and maximum uptime - improving patient outcomes and lowering TCO.

FEATURES AND BENEFITS



Superior 1D and 2D scanning performance, even on damaged and poor-quality barcodes, eliminates wasted seconds from any scan.



The disinfectant-ready plastic housing protects your investment with a durable construction engineered to resist the harmful effects of harsh chemicals.



Multiple patient comfort modes are available to ensure patient comfort while maintaining clinician productivity: Patient Do-Not-Disturb, Vibration, and Scan Lamp.



Honeywell Operational Intelligence software delivers on-demand scan insights, enabling higher healthcare worker productivity and throughput.



The Honeywell Scanner Management Utility (SMU) creates a holistic solution that automates how you deploy and update the scanners in your environment.

Honeywell

Xenon Extreme Performance (XP) 1952h Technical Specifications

WIRELESS

Radio/Range: 2.4GHz Bluetooth radio v4.2 with Adaptive Frequency Hopping. Class 1: 100m line of sight (default), programmable to Class 2: 10m line of sight

Power Options:

Battery: 2400 mAh Li-ion minimum

Number of Scans: Up to 72,000 scans per charge

Expected Duration of Operation: 20 hours

Expected Charge Time: 4.5 hours

User Indicators: Good Decode LEDs, Rear View LEDs, Beeper (adjustable tone and volume), Vibration (adjustable), Charge Status Indicator

MECHANICAL/ELECTRICAL

Dimensions (L x W x H):

Scanner: 104.1 mm x 71.1 mm x 160 mm (4.1 in x 2.8 in x 6.3 in)

Presentation Base: 132 mm x 101 mm x 81 mm (5.2 in x 4.0 in x 3.2 in)

Desktop/Wall Mount Base: 231 mm x 89 mm x 83 mm (9.1 in x 3.5 in x 3.3 in)

Weight:

Scanner: 212.62 g (7.5 oz)

Presentation Base: 179 g (6.3 oz)

Desktop/Wall Mount Base: 260 g (9.2 oz)

Operating Power (Charging) Bases: 2.5 W (500 mA @ 5V DC)

Non-Charging Power (Bases): 0.75 W (150 mA @ 5V DC)

Host System Interfaces: USB, Keyboard Wedge, RS-232, IBM 46xx (RS485)

ENVIRONMENTAL

Operating Temperature:

Scanner: 0°C to 50°C (32°F to 122°F)

Bases:

Charging: 5°C to 40°C (41°F to 104°F)

Non-Charging: 0°C to 50°C (32°F to 122°F)

Storage Temperature: -40°C to 70°C (-40°F to 158°F)

Electrostatic Discharge (ESD) (Scanners and Cradles): ±8 kV indirect coupling plane, ±15 kV direct air

Humidity: 0 to 95% relative humidity, non-condensing

Tumble Spec: 2,000 0.5 m (1.6 ft) tumbles (impacts)

Drop: Engineered to withstand 50 1.8 m (6 ft) drops to concrete

Environmental Sealing (Scanner): IP52

Light Levels: 0 to 100,000 lux (9,290 foot-candles)



SCAN PERFORMANCE

Scan Pattern: Area Image (1280 x 800 pixel array)

Motion Tolerance: Up to 400 cm/s (157 in/s) for 13 mil UPC at optimal focus

Scan Angle:

HD: Horizontal: 48°; Vertical: 30°

SR: Horizontal: 48°; Vertical: 30°

Print Contrast: 20% minimum reflectance difference

Roll, Pitch, Skew: ±360°, ±45°, ±65°

Decode Capabilities: Reads standard 1D, PDF, 2D, Postal Digimarc, DOT Code, and OCR symbologies

(Note: Decode capabilities dependent on configuration.)

Warranty: Three-year factory warranty

(Note: Battery Pack warranty is one year.)

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.

Xenon is a trademark or registered trademark of Honeywell International Inc.

All other trademarks are the property of their respective owners.

DECODE RANGES (DoF)

TYPICAL PERFORMANCE*	STANDARD RANGE (SR)	HIGH DENSITY (HD)
NARROW WIDTH		
3 mil Code 128	56 mm - 132 mm (2.2 in - 5.2 in)	27 mm - 131 mm (1.1 in - 5.1 in)
5 mil Code 39	28 mm - 242 mm (1.1 in - 9.5 in)	14 mm - 219 mm (0.6 in - 8.6 in)
10 mil Code 39	0 mm - 443 mm (0 in - 17.4 in)	0 mm - 389 mm (0 in - 15.3 in)
13 mil UPC	0 mm - 490 mm (0 in - 19.3 in)	0 mm - 368 mm (0 in - 14.5 in)
15 mil Code 128	0 mm - 543 mm (0 in - 21.4 in)	0 mm - 417 mm (0 in - 16.4 in)
20 mil Code 39	4 mm - 822 mm (0.1 in - 32.4 in)	6 mm - 604 mm (0.2 in - 23.8 in)
5 mil PDF417	54 mm - 160 mm (2.1 in - 6.3 in)	30 mm - 155 mm (1.2 in - 6.1 in)
6.7 mil PDF417	34 mm - 220 mm (1.4 in - 8.7 in)	17 mm - 211 mm (0.7 in - 8.3 in)
7.5 mil DM**	49 mm - 172 mm (1.9 in - 6.8 in)	27 mm - 160 mm (1.0 in - 6.3 in)
10 mil DM**	29 mm - 245 mm (1.1 in - 9.7 in)	12 mm - 211 mm (0.5 in - 8.3 in)
20 mil QR	0 mm - 438 mm (0 in - 17.2 in)	0 mm - 331 mm (0 in - 13.0 in)

* Performance may be impacted by barcode quality and environmental conditions.

** Data Matrix (DM)