

6MP CW60



14-Bit RGB Color



LED Backlight



High Brightness



Self-Brightness Control (SBC)



Luminance Uniformity Control



Multi-functional Stand-base



DICOM Sensor (IQ Sensor® II)



2 Displayport



5 Years Warranty



WIDE

Maximum Visual Precision

The CW60 is the new medical imaging display solution with highly advanced TFT LCD technology; higher brightness, better contrast ratio, real black uniformity performance and perfect image quality in color and grayscale. Both color and grayscale images can be viewed with the comfort of preset DICOM-modes, enabling to review images from different medical sources in optimal conditions, improving efficiency and diagnostic performance significantly. The CW60 brings better image quality, DICOM Calibration and advanced quality control, within reach while making life critical decisions.

CW60 6M Color Monitor

- True 10-bit TFT LCD
- LED Backlight
- 14-bit RGB Color
- IQ-Sensor® / SBC Sensor



A better image quality can make a life critical difference when it comes to making a diagnosis. WIDE has developed this display to produce the highest-quality images and most comprehensive tools, because every life is precious.

LCD Panel	TFT AMLCD IPS Grayscale, True 10-bit RGB Color, LED Backlight
Native Resolution	3280(H) x 2048(V)
Pixel Pitch	0.187mm x 0.187mm
Active Display Area	613.8mm x 383.2 mm (24.2"x15.1")
Active Screen Size (Diagonal)	28.5"
Viewing Angle (Typical)	178°(H) x 178°(V) at 10:1 Contrast Ratio
Brightness Max.	800cd/m ²
Brightness Calibrated	500cd/m ²
Contrast Ratio (Typical)	800:1
Bit-rate for Look-up Table	14-bit
Luminance Uniformity Correction	5 Levels selectable between Min and Max
DICOM View Mode	Mammography Normal, Mammography High, CT/MRI, Ultrasound, User
Digital Video Input	DVI-D (2x) and DisplayPort (2x)
Display Communication	DDC2B (VESA Standard Compliance)
Built-in Sensors	IQ Sensor®, Self-Brightness Control(SBC), Digital Ambient Control(DAC)
Private LED Lamp	Yes (PrivateLite®)
Universal Serial Bus(USB)	1 up and 3 down-streams
Display Adjustments	Haptic Buttons (Menu, Enter, Left, Right, DICOM), Power On/Off
OSD Languages (9 languages)	English, German, French, Spanish, Italian, Russian, Chinese, Japanese, Korean
Input Power	AC Input 100-240Volt+/-10%, 60Hz/50Hz+/-3Hz
Power Consumption	Max: 210 Watts / Power Save Mode: less than 2 watt
Dimension	738.0mm(W) x 609.0mm(H) x 302.5mm(D) (29.0" x 23.97" x 11.9")
Weight	With Stand-base: 22Kg (48.50lb) / Without Stand-base: 16Kg (35.27lb)
Tilt/Swivel/Height Adjustment	-3°, +15°/+90°, -90°/103mm
Mounting Hole	VESA Standard (100x100mm)
Operational Temperature	0°C to 40°C (32°F to 104°F)
Operational Humidity	30% to 80%
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Certifications and Standards	FCC Class B, CE, VCCI Class B, KCC, ICES-003-B, C-Tick UL60601-1, CSA Std., C22.2 No.601.1, IEC/EN60601-1, FDA 510 (Pending)

Contact

WIDE KOREA

456, Gomae-dong, Giheung-gu, Yongin-si, Gyeonggi-do, 446-901, Korea
Tel: +82-31-218-1600 Fax: +82-31-274-7400 info@widecorp.com

WIDE USA

8 Hammond St., Suite #114 Irvine, CA 92618, USA
Tel: +1-949-305-9933 Fax: +1-949-305-5452 infousa@widecorp.com

WIDE EUROPE B.V.

Hullenbergweg 413, 1101 CS Amsterdam, Zuidoost, The Netherlands
Tel: +31-20-311-9797 Fax: +31-20-311-9790 infoeu@widecorp.com

WIDE JAPAN

6th fl, Shinjuku Suzuki Bldg A 1-6-8 Shinjuku, Shinjuku-Ku, Tokyo160-0022, Japan
Tel: +81-3-6457-8371 Fax: +81-3-6457-8372 infojapan@widecorp.com

Specifications and features are subject to change without notice. Images shown are for illustrative purpose only. All products names are trademarks or registered trademarks of WIDE Corp. This document is copyrighted. Neither this document, nor any part of it, may be reproduced or copied without written permission of WIDE Corp. | Printed in Korea. 2013. 03. Ver 1.0